

(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 279 425 A2

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
29.01.2003 Bulletin 2003/05

(51) Int Cl.⁷: **A63F 13/10**

(21) Application number: **02016211.1**

(22) Date of filing: **18.07.2002**

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SK TR**
Designated Extension States:
AL LT LV MK RO SI

- Okubo, Toru
Minato-ku, Tokyo (JP)
- Domitsu, Hideyuki
Minato-ku, Tokyo (JP)
- Yamano, Tomoya
Minato-ku, Tokyo (JP)

(30) Priority: **19.07.2001 JP 2001220312**

(71) Applicant: **Konami Corporation**
Minato-ku, Tokyo (JP)


(74) Representative: **Müller-Boré & Partner**
Patentanwälte
Grafinger Strasse 2
81671 München (DE)

(72) Inventors:
• Oishi, Toshimitsu
Minato-ku, Tokyo (JP)

(54) **Video game apparatus, method and recording medium storing program for controlling movement of simulated camera in video game**

(57) A 3-dimensional video game apparatus comprises display 40 for displaying an image; image-processing means 16 for creating a 3-dimensional image from the viewpoint of a simulated camera and displaying that image on a display screen; and game controller 14 which conducts the game in response to reactions of the player, responsive to images displayed on display 40. The game apparatus further comprises camera unit 42 which can be arranged in such an orientation that its field of view is the play area in front of the display screen, and which periodically captures images of the play area in the state thus arranged; a position recognizing part which detects the player's head from the captured image, and detects the two-dimensional movement of the detected head position; and viewpoint change processor which moves the viewpoint of said simulated camera in conjunction with the change direction and change amount of the position of the detected marked region.

FIG.1



EP 1 279 425 A2

Description

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0001] The present invention relates to a video game control technique whereby game images from the viewpoint of a simulated camera, for example a 3-dimensional images, are created and displayed on a display screen and, while varying the viewpoint of a simulated camera, the game is conducted by receiving reactions from a player who is responding to images displayed on the above-mentioned display.

2. Description of the Related Art

[0002] Coin-operated game machines, wherein a camera is affixed to an appropriate location on the game cabinet and this camera captures the image of a player, who is playing in front of a game scene displayed on the monitor, are already known. In such game machines, the player's movement is confirmed by image capture of a special detectable object mounted on the player (and suitable for being image-captured by the camera). With these game machines, movement of the human body is detected from the image of the detectable object which is image-captured by the camera, and the game proceeds, developing in response to that movement. In addition, coin-operated games are known in which one ultrasound transmitter and two ultrasound receivers are mounted on top of the player's head, an ultrasound pulse transmitted by the transmitter is reflected by the player's head and the head position is calculated from the propagation times of the ultrasound pulses received by each of the two receivers and the time difference between them. In these games, the viewpoint of a simulated camera, which is the reference for generating simulated 3-dimensional game scenes, is linked to the calculated head position.

[0003] In contrast, unlike the case of coin operated games, it is difficult to achieve home video games which provide game scenes having a feeling of realism, through linking the viewpoint of the simulated camera to the player's movement. For example, a fixed and invariable play area cannot be assured, as it can in the case of coin-operated games, so there is the problem of processing the varied background images included in the captured image according to place and time. Furthermore, there is a limit to how strongly a player can be urged to buy the special "detectable object" which, as mentioned above, is easily detectable in a captured image.

SUMMARY OF THE INVENTION

[0004] With the foregoing in view, it is an object of the present invention to provide a video game apparatus

wherein an image capture means is positioned in the desired position with its orientation such that its field of view is the play area in front of the display screen and wherein the viewpoint of above-mentioned simulated camera is moved, linked to the change direction and change amount of the marked region based on the captured images. It is also an object of the present invention to provide a method and program for controlling movement of the simulated camera viewpoint in a video game.

[0005] The one aspect of the present invention relates to a video game apparatus comprising: a display for displaying images; a display control means for creating game images as seen from a simulated camera viewpoint and displaying said images on the screen of the display; and a game control part for conducting the game in response to reactions of a player responsive to the images displayed on the display; an image capture means which can be arranged in such an orientation that its field of view is the play area in front of the display screen, and which periodically captures an image of the play area in the state thus arranged; a position detecting means for detecting from the captured images the position of a player's marked region; a movement detecting means for detecting two-dimensional movement of the position of the marked region thus detected; and a viewpoint changing means for moving the simulated camera viewpoint, in accordance with the change direction and change amount of the position of the detected marked region.

[0006] These and other objects, features and advantages of the present invention will become more apparent upon reading the following detailed description along with the accompanied drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0007]

Fig. 1 is a diagram showing a player using a game apparatus according to an embodiment of the present invention and enjoying a gun-shooting game;

Fig. 2 is a diagram showing the hardware configuration of the game apparatus;

Fig. 3 is a diagram showing the software configuration of the microprocessor of the game apparatus;

Figs 4A to 4D consist of several diagrams which illustrate an example of a game scene showing the case of a player moving in an up-down direction;

Figs. 5A to 5D consist of several diagrams which illustrate an example of a game scene showing the case of a player moving in a transverse direction;

Fig. 6 is a diagram showing an example of a title screen (start screen);

Fig. 7 is a flow diagram describing title screen display processing;

Fig. 8 is a diagram illustrating an example of the

"player standing position guide" image included in the title screen;

Fig. 9 is a diagram showing a variation of the "player standing position guide" image included in the title screen;

Fig. 10 is a diagram describing processing of the player image;

Fig. 11 is a diagram describing filter processing related to the recognized position;

Figs. 12A to 12D are diagrams showing a series of player images;

Fig. 13 is a diagram showing the differential image between the newest image and an averaged image;

Fig. 14 is a diagram showing the results of extracting the previously recognized position neighborhood from the image shown in Fig. 13;

Fig. 15 is a diagram showing the differential image between the newest image and an averaged image in the case that player movement is small;

Fig. 16 is a diagram showing the results of extracting the previously recognized position neighborhood from the image shown in Fig. 15;

Fig. 17 is a diagram showing the differential image between the newest image and the immediately preceding image;

Fig. 18 is a diagram showing the result of extracting the previously recognized position neighborhood from the image shown in Fig. 17;

Fig. 19 is a diagram showing the differential image between the newest image and the immediately preceding image, in the case that the previously recognized position is separated from the newest player image and the immediately preceding player image;

Fig. 20 is a figure showing the result of extracting, from the image shown in Fig. 19, a position closer to the player from the previously recognized position; and

Figs. 21 A and 21 B are diagrams showing the memory content of the "recognized position" buffer.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0008] Fig. 1 is a perspective view illustrating the situation of a player using a game apparatus according to an embodiment of the present invention and playing a game. As shown in the same figure, the game apparatus is configured including home-use TV receiver 40 as a display, camera unit 42 as an image capturing means, home video game machine 46, and gun controller 48, and is a device for achieving a gun shooting game.

[0009] Home-use TV receiver 40 and home video game machine 46 are, for example, mounted on cabinet 44, and camera unit 42 in the present embodiment is mounted on top of home-use TV receiver 40. Camera unit 42 is a digital camera which captures images of the player's stance in real time and is connected to home-

use game machine 46 by a cable. The digital camera has photoacceptor elements, such as charge coupled devices (CCD's), positioned in a 2-dimensional arrangement at the imaging position on the optical axis of a photographic lens and, with the proper exposure time, it acts as a device which captures optical images of the objects in the field of view (the player).

[0010] Home-use game machine 46 is connected to home-use TV receiver 40 which displays the game scenes generated by home-use game machine 46 and outputs the game music and game sound effects. In addition, it is arranged that, when performing normalizing processing of the standing position, the image of the player which was image-captured is provided in real time to home-use game machine 46. Gun controller 48 is a pistol-shaped game controller and is connected to the controller connection terminal of home-use game machine 46 by a cable. Player P holds gun controller 48 in his hand and when he points it at home-use TV receiver 40, its barrel direction is inputted into home-use game machine 46. In addition, gun controller 48 is provided with a trigger, and a signal indicating trigger status (trigger pulled or not) is inputted into home-use game machine 46.

[0011] With family-use video game machine 46, a 3-dimensional game space (virtual 3-dimensional space) is built in memory and it is arranged that the appearance of viewing the 3-dimensional space from the viewpoint of a simulated camera located at a specified spatial position is displayed on home-use TV receiver 40. At this time, home-use game machine 46 confirms the position of player P's head from the player image and performs viewpoint change processing to link above-mentioned viewpoint position to player's head position. As a result, when player P moves his body in front of camera unit 42, the game scene displayed on home-use TV receiver 40 changes in response to that, and player P can get a sense just as though he himself had entered into the 3-dimensional game space (a sense of "being there.") In this way, with home-use game machine 46, a game is achieved wherein player P, using gun controller 48, shoots the enemy characters who appear in the 3-dimensional game space and player P, by moving his body (specifically his head position), can dodge the incoming attack (shots) of the enemy characters.

[0012] Fig. 2 is a diagram showing the hardware configuration of game apparatus 10. As shown in that diagram, game apparatus 10 is configured by mounting DVD (Digital Versatile Disk, trademark) unit 25, which serves as an information storage medium, on home-use game machine 46, which is connected to monitor 18 and speaker 22, which are part of home-use TV receiver 40. Here, for supplying game programs and game data to home-use game machine 46, DVD unit 25 is used, but any other kind of information storage medium, such as CD-ROM (Compact Disk - Read Only Memory, trademark) or ROM (Read Only Memory) card, etc. could be

used. In addition, it is possible to supply game programs and game data to home-use game machine 46 from a distant location, via a data communication network, such as the Internet.

[0013] Home-use game machine 46 is configured including microprocessor 14, image processor 16, main memory 26, input/output processor 30, peripheral device interface 31, audio processor 20, and DVD playback part 24. Microprocessor 14, image processor 16, main memory 26, input/output processor 30, and peripheral device interface 31 are connected by means of bus 12 which enables mutual data communication. Gun controller 48, audio processor 20, and DVD playback part 24 are connected to input/output processor 30. In addition, camera unit 42 is connected to peripheral device interface 31. The various elements which make up home-use game machine 46 are contained within a cabinet. Here, as monitor 18, home-use TV receiver 40 is used, and as speaker 22, its internal speaker is used.

[0014] Microprocessor 14 controls each part of home-use game machine 46 based on an operating system stored in a ROM (not shown in the figure) and the game program read out from DVD 25. Bus 12 is for the exchange of addresses and data between the various parts of home-use game machine 46. In addition, game programs and game data read out from DVD 25 are written into main memory 26 as necessary. Image processor 16 is configured including VRAM (Video Random Access Memory) and, receiving image data sent from microprocessor 14, plots game scenes in VRAM. Image processor 16 also converts that content into video signals and outputs them to monitor 18.

[0015] Image processor 16 calculates the coordinate positions, etc. of each character (enemy characters, physical "characters" such as the various buildings positioned in the game space, etc.) viewed from the viewpoint of the simulated camera within the simulated 3-dimensional space. From the calculated coordinate positions in the simulated 3-dimensional space, image processor 16 also performs the calculations for converting to coordinate positions in 2-dimensional space and performs positioning processing of the polygons which constitute the images to be plotted in the display buffer of main memory 26. In addition, image processor 16 performs texture mapping in regard to each polygon. As information on the viewpoint of the simulated camera for calculation of character coordinate positions, position information on the player's marked region for example his head, is transmitted from position recognizing part 71 which will be explained later. Consequently, the viewpoint of the simulated camera substantially matches the eye of the player, and in this embodiment, a character corresponding to the player does not appear on the monitor screen.

[0016] Input/output processor 30 is an interface for relaying data communications between gun controller 48, audio processor 20, DVD playback part 24, and microprocessor 14. As shown in Fig. 1, gun controller 48 is a

pistol-shaped game controller and is used for inputting into home-use game machine 46 the trigger status and barrel (muzzle) direction (specifically, the position on the screen of home-use TV receiver 40 at which the barrel is pointed). For gun controller 48, a commonly known configuration can be used, for example. In other words, when player P pulls the trigger of gun controller 48, that information (trigger signal) is inputted into home-use game machine 46 from the controller terminal. Then, in home-use game machine 46, when that trigger signal is inputted, by means of the game program, for example, a scene of a specific color (for example, white) is displayed for just one frame, and as a result, a spot is scanned on the screen of home-use TV receiver 40. By providing a highly directional photosensor deep inside the barrel of gun controller 48 and, with that sensor, detecting the spot on home-use TV receiver 40, the time from the instant of starting the scan to the instant of detecting the spot is calculated and, from that, the position (coordinates) of the spot on the screen of home-use TV receiver 40 is calculated. Then, by inputting that position, in other words the direction of the gun barrel, into home-use game machine 46, gun controller 48 can be suitably achieved. Note that it is best if the instant of starting the scan is obtained from a synchronization signal included in the video signal supplied from home-use game machine 46 to home-use TV receiver 40.

[0017] Then, calculation of the trajectories of bullets shot by the player through the game space of the screen of TV receiver 40 is performed in order; and preferably, for each calculation, by displaying the bullet in the scene or by a like means, it can be judged whether an enemy character in the scene has been hit or not. The decision as to whether or not there has been a hit is made by finding a coordinate match, or a substantial coordinate match, between the results of successive bullet trajectory calculations and enemy character position coordinates.

[0018] Audio processor 20 is configured including a sound buffer, and data such as music, game sound effects, etc., which have been read out from DVD 25 and stored in the sound buffer are played back and outputted from speaker 22. DVD playback part 24, in accordance with instructions from microprocessor 14, reads out game programs and game data stored in DVD 25. Peripheral device interface 31 is an interface for connecting various peripheral devices to home-use game machine 46 and can use a USB (Universal Serial Bus) interface, for example. In this case, camera unit 42 is connected to peripheral device interface 31. Camera unit 42 is, for example, a commonly known digital camera for inputting gray scale photographic images (256 gradations of black and white) into home-use game machine 46 at specified time intervals (for example, every 1/60th of a second, etc.) In the present case, in order to image capture the stance of player P, this camera unit 42 is mounted on top of home-use TV receiver 40 in the state where its lens is pointed at player P.

[0019] Here will be explained the processing done by home-use game machine 46 for displaying the title screen. This processing is executed based on the game program stored in DVD 25.

[0020] Fig. 3 is a diagram showing the software configuration of the microprocessor 14. In Fig. 3, microprocessor 14 comprises initial play position setup part 70, position recognizing part 71, filter processing part 72 and viewpoint change processor 73. The functions of each part are performed based on the game program stored in DVD 25. Position recognizing part 71 comprises the several parts from image capture control part 7111 to center of gravity calculating part 7123. Filter processing part 72 comprises the several parts from information updating part 7211 to buffer size determining part 7214.

[0021] Initial play position setup part 70 is a means for performing initial calibration processing to normalize the player's standing position. Thus, as shown in Fig. 6, in a specified position on monitor 18, it displays "player standing position guide image" 50 and in a specified position in that image 50, which in the present embodiment is slightly above the center, it displays "head reference position marker" 52 shown, for example, by a circular marker. It also displays, superimposed on the above image, player image 56, image-captured by camera unit 42, and "present recognized position marker" 54, obtained from that image 56 and shown, for example, as a round dot. By changing the standing position or stance of player P, or the photographing direction or photographing position of camera unit 2, present recognized position marker 54 moves into circularly-shaped head reference position marker 52. Whereupon the display appearance of head reference position marker 52 is changed (for example, turning ON or OFF a colored or flashing display) indicating that the reference position (initial play position) has been normalized.

[0022] Next, in Figs. 4A through D, is shown a series of game scenes displayed on home-use TV receiver 40 for the case that player P's head moves in an up-down direction. In Figs. 4A through 4D of the same figure, four scenes are shown in the order of their display for the case that player P, in front of camera unit 42, rises from a crouched stance gradually to an almost fully upright stance--in other words, for the case that player P's head moves from a lower position to a higher one. In the game scene shown in Fig. 4A of the same figure, table-shaped barrier B exists immediately in front of the viewpoint, expressing the situation that player P is hiding in front of the lower part of this barrier B. In this case, only a part of the head of enemy character AC1, who is behind barrier B holding a gun in his hand, appears in the game scene. Next, the game scene shown in Fig. 4B of the same figure shows the situation where player P has raised his head a small amount, so that the level of his head is about the same as that of the upper surface of barrier B. In this case, enemy character AC1 becomes visible down to his chest while behind him the heads of

two more enemy characters, AC2 and AC3, newly appear in the game scene. The game scene shown in Fig. 4C of the same figure shows the situation where player P has straightened up more and raised his head. In this case, player P's head is in a slightly higher position in the game scene than the barrier upper surface Bs. The upper bodies of the three enemy characters, AC1 through AC3, are visible and the barrier upper surface Bs also appears. The game scene shown in Fig. 4D of the same figure shows the situation where player P is essentially in a fully upright stance. In this case, the head and shoulders of player P are exposed above barrier B and barrier upper surface Bs is visible to a greater extent than in the game scene shown in Fig. 4C of the same figure. As shown in these figures, as the position of player P's head rises, the display position of barrier B moves lower, and a more complete view of barrier upper surface Bs and enemy characters AC1 through AC3 gradually appears in the game scene.

[0023] Next, Figs. 5A through 5D show an example of a series of game scenes displayed on home-use TV receiver 40 in the case that player P's head moves in a right-left direction. In Figs. 5A through 5D of the same figure, four scenes are shown in the order of their display for the case that player P, in front of camera unit 42, moves his body from the right side to the left side, in other words, for the case that player P's head moves from the right side to the left side. In the game scene shown in Fig. 5A of the same figure, door- or wall-shaped barrier B exists immediately in front and at the right side of the viewpoint, expressing the situation that player P is hiding in front of this barrier B. In this case, only a part of the arm of enemy character AC1, who is behind barrier B holding a gun in his hand, appears in the game scene. Next, the game scene shown in Fig. 5B of the same figure shows the situation where player P has moved to the left somewhat, so that his head is about even with left edge of barrier B. In this case, the head and chest of enemy character AC1 become visible in the game scene. The game scene shown in Fig. 5C of the same figure shows the situation where player P has moved further to the left. The upper body of enemy character AC1 becomes visible and enemy character AC2 also appears behind him. The game scene shown in Fig. 5D of the same figure shows the situation where player P is essentially in a fully upright stance. In this case, player P has jumped out to the left from barrier B and, in addition to enemy game characters AC1 and AC2, enemy game character AC3 has additionally appeared.

[0024] As shown in these figures, as the position of player P's head moves from left to right, the display position of barrier B moves to the right side and correspondingly the display position of barrier B moves to the right and full views of enemy characters AC1 through AC3 gradually appear.

[0025] Fig. 6 is a diagram showing an example of the game title screen (start screen) supplied by home-use

game machine 46. The title screen shown in the same figure is displayed on home-use TV receiver 40 after start up of home-use game machine 46 or after game completion and before the start of a new game. As shown in the same figure, on both sides of the screen in this title screen, images of menu buttons are displayed and in the upper part of the center, game title text line 60 is displayed. In addition, under title text line 60, player "standing position guide image" 50 is displayed. In addition, menu buttons 62 are objects to be operated to select various games or set options, and when player P, by means of controller 48 shoots menu button image 62, the game or option setting corresponding to that menu button image 62 is started.

[0026] Player "standing position guide image" 50 is displayed by means of initial play position setup part 70 and is an image for assisting player to normalize his standing position prior to game start. Prior to start of the game, player P, looking at this same "standing position guide image" 50, corrects his standing position or stance in front of camera unit 42 or corrects the picture-taking angle or position of camera unit 42. Initial play position setup part 70, based on real-time images acquired by camera unit 42 from image capture controller 7111, in other words, based on player image 56, aligns and displays head reference position marker 52 and present recognized position marker 54. Head reference position marker 52 is a circular mark displayed in a fixed position of player image 56 (for example in the center of player image 56 at a position 15% from the top, etc.) Its purpose is to show the location in player image 56 where the image position of player P's head (top part of his head) should be aligned, prior to start of the game. Likewise, with this game apparatus 10, it is arranged that the present position of player P's head can be recognized from player image 56 and the circular dot indicating that recognized position is displayed superimposed as "present recognized position marker" 54 on player image 56. Player P, by moving his own body (standing position or stance) or changing the picture-taking direction or position of camera unit 42, can make present recognized position marker 54 move into circular head reference position marker 52. Initial play position setup part 70 determines whether present recognized position marker 54 is displayed inside head reference position marker 52. It is made so that, depending on that result, it changes the display appearance of head reference position marker 52 (for example, turning ON or OFF a color or flashing display). In this way, it is arranged that player P, while viewing player standing position guiding image 50, can readily normalize the positional relationship of himself and camera unit 42, prior to start of the game.

[0027] Here is explained the processing of home-use game machine 46 for displaying the title screen. This processing is performed based on the game program which has been stored in DVD 25.

[0028] Fig. 7 is a flow diagram describing game title screen display processing by home-use game machine

46. As shown in the same figure, with home-use game machine 46, first, microprocessor 14 plots the background image of the title screen, title text line 60, menu button images 62, copyright indication, etc. into VRAM which is included in image processor 16 (S101). Next, the image to be captured by camera unit 42 (here, the object is to photograph player P, so this is called a "player image") is captured (S102). Then, the player image captured in S102 is plotted into VRAM (S103), so that the player image is positioned in the "player standing position guide image" 50 position in the title screen.

[0029] Further, based on the player image captured in S102, the position of player P's head (head position) is recognized and information after filter processing the recognition results (filter processed head position) is acquired (S104). The position recognition processing and filter processing mentioned here will be explained in detail later. Afterward, microprocessor 14 draws the "present recognized position marker" 54 at the VRAM coordinates corresponding to the filter processed head position (S105), so that a marker (red point) is displayed at head position of the player image included in the title screen.

[0030] Next, initial play position setup part 70 determines whether the filter processed head position is in the reference position. The reference position is the position in the player image where player P's head should appear prior to start of the game. Then, if the filter processed head position is in the reference position, a red-colored head reference position marker 52 is plotted at the reference position of the player image already plotted in the VRAM (S107). On the other hand, if the filter processed head position is not in the reference position, a blue-colored head reference position marker 52 is plotted at the reference position of the player image (S108). Afterward, the gun barrel direction of gun controller 48 is acquired (S109), and aiming marker is 58 is drawn in that position (S110).

[0031] If the above is done, in the case that the positional relationship between player P and camera unit 42 is not appropriate, as shown in Fig. 8, "present recognized position" marker 54 will be displayed outside circular head reference position marker 52 in the title screen and head reference position marker 52 will be displayed in blue. On the other hand, in the case that the positional relationship between player P and camera unit 42 is appropriate, as shown in Fig. 6, "present recognized position" marker 54 will be displayed inside circular head reference position marker 52 in the title screen and head reference position marker 52 will be displayed in red. In this way, by changing his standing position or changing the mounting position or camera-direction of camera unit 42, so that head reference position marker 52 is made to be displayed in red in the title screen, player P can readily normalize the positional relationship between himself and camera unit 42.

[0032] If the positional relationship between player P and camera unit 42 is not normalized, when player P

bends, stoops or shifts his body right or left during the game, his head position may not fit into the player image with the result that the correct head position could not be recognized. However, with present game apparatus 10, the positional relationship of player P and camera unit 42 can be normalized prior to start of the game. As a result, even when player P bends, stoops or shifts his body left or right during the game, his head position can be correctly recognized.

[0033] Note that the guidance given to player P need not be limited to that explained above. For example, as in the guidance image shown in Fig. 9, it is acceptable to display only present recognized position marker 54 and head reference position marker 52, without displaying the player image. In addition, instead of changing the display appearance of head reference position marker 52 according to the positional relationship of present recognized position marker 54 and head reference position marker 52, it is acceptable to change the display appearance of present recognized position marker 54 (color or flashing pattern). Alternatively, it is acceptable to provide a display in a separate location, responsive to the positional relationship of present recognized position marker 54 and head reference position marker 52. It is also acceptable to omit display of the present recognized position marker 54.

[0034] Furthermore, it is also acceptable to display only present recognized position marker 54 and to change the display appearance of present recognized position marker 54 when present recognized position marker 54 moves into the position where head reference position marker 52 should properly be displayed. Even if this approach is taken, player P can correct the positional relationship between himself and camera unit 42 while watching the guidance image.

[0035] In addition it is acceptable if the arrangement is that, according to the relationship between the present recognized position of player P's head and the reference position, a message, for example "Please move to the right," or "Please move to the left" or "Please move forward," or "Please move backward," is displayed. Also, the shapes of present recognized position marker 54 and head reference position marker 52 are not limited to those described above, but a variety of kinds of shapes can be adopted. Furthermore, the guidance for player P can be provided prior to start of the game. To do that, the guidance for player P may be provided, for example, on a different screen from the title screen.

[0036] Next will be explained player image processing in home player game machine 46.

[0037] Fig. 10 is a flow chart which describes the processing which, based on the player image acquired from camera unit 42, subject to control by the image capture control part, recognizes the head position of player P and performs filtering of the recognition results. Likewise, Fig. 11 is a flow chart which describes the filter processing in detail. In accordance with the game pro-

gram stored in DVD 25, the various processing is executed in home-use game machine 46, at specified time intervals (for example, every 1/60th of a second) as controlled by timer 7112.

5 [0038] When the player image has been acquired by camera unit 42, captured image fetching part 7113, as shown in Fig. 10, first stores that player image in an image buffer prepared in main memory 26 (S201). This image buffer is for the purpose of storing in memory the images acquired by camera unit 42 at specified time intervals. It stores in time sequence, a specified number of (here, a total of 4) player images, including the newest player image. Then, when the newest player image is acquired, that player image is added to the image buffer and at the same time the oldest player image is discarded. Fig. 12 is a diagram showing a series of player images stored in the image buffer. In the sub-figures of Fig. 12, the following are shown: in Fig. 12A of that figure, the newest player image; in Fig. 12B of the same figure, the preceding player image; in Fig. 12C of the same figure, the player image preceding that one; and in Fig. 12D of the same figure, the player image even preceding that one (that is, the oldest player image in the buffer). The example shown in that figure shows the situation where player P sways his body from left to right in front of camera unit 42.

20 [0039] Next, averaging processor 7114 generates an average of the three player images which are the player images stored in the image buffer excepting the newest image (S202). In this embodiment, the averaged image is an image obtained by averaging the color information (256 monochrome gradations) given to each picture element [pixel] corresponding to the three player images. As will be explained later, this number, 3, has been found to be suitable experientially and experimentally, based on the movement of player P and the image-fetching period of 1/60th of a second. Then, by means of first differentiator/binary converter 7115, the difference between this averaged image and the newest player image is generated (S203). This differential image is the image obtained by subtracting the color information given to the corresponding pixels in these two images, magnitude-comparing it to a threshold value, and converting it to binary (to monochrome). Fig. 13 is one example of this differential image. Then, by means of image extractor 7116, an image with a specified radius centered on the previous recognized position (the position of player P's head) is extracted from this differential image (S204). Fig. 14 is an example of this extracted image. In this drawing, the black dot shows the previous recognized position and in fact, it is not shown in the extracted image.

55 [0040] Next, area determining part 7117 checks whether or not the area of the region shown in black in the extracted image (the region where a difference remains) is below a specified threshold or not (S205). Then, if the area of the region shown in black in the extracted image is below the specified threshold, re-out-

putting part 7118 re-outputs the previous output (filter processed head position) which has been stored ahead of time in main memory 26 (S213). In the case that player P's amount of movement is small, as shown in Fig. 15, only a differential part corresponding to player P's outline remains as the differential image obtained in S203. In this case, by extracting the neighborhood of the previous recognized position, that area becomes small, as shown in Fig. 16. In the processing from S202 to S205, when, as shown in Fig. 16, the amount of movement is small, the previous output is re-outputted and changing of the output value is suppressed.

[0041] On the other hand, in the case that the area shown in black in the extracted image exceeds a certain threshold, next the newest player image (in Fig. 12A) and the player image immediately preceding that (in Fig. 12B) are read out of the image buffer, and a differential image of them (image converted to binary) is generated (S206) by means of second differentiator/binary converter 7119. Fig. 17 is a diagram showing one example of this differential image. Then, from this differential image, image extractor 7116 extracts an image (the selected image) of a specified radius centered on the previously recognized position. This specified radius may be the same as the previously described specified radius adopted for use in the decision-making of area determining part 7117, or it may be set at a somewhat larger value, considering that the amount of motion may be large. Fig. 18 shows an example of this extracted image. In this figure, the black circular dot indicates the previous recognized position and it is not actually displayed in the extracted image. The position of the pixels shown in black in the extracted image is used in recognizing the head location of player P in S211. In other words, this extracted image includes the foundation position group at the time that head position of player P is recognized. Then, player head position is found from the foundation position group pixels.

[0042] Change amount calculator 7120 calculates the amount of change in the region shown in black in this extracted image (foundation position group; region where difference remains). According to the present embodiment, height and width are measured, and those values are respectively checked by change determining part 7121 as to whether or not they are under specified threshold values (S208). If it is found by change determining part 7121 that either of these values is below the specified threshold, the extracted range (selected range) is moved by image movement processor 7122 in the direction of player P until the extracted range (selected range) is sufficiently close to player P (S209) and the extracted image is regenerated (S210). Specifically, the center of gravity of the region shown in black in the differential image of S206 (image converted to binary) is calculated by center of gravity calculator 7123 and the center of the extracted range (selected range) is moved in specified distance increments from previous recognized position toward that center of gravity. Fig. 19 is a

diagram for explaining the nature of that processing. In it, the region which has been hatch marked is the region where a difference remains and the black triangle indicates the position of the center of gravity of the differential portion, while the black dot indicates the previous recognized position. The same figure shows the appearance of a sudden movement of player P from the upper left to the lower right in front of camera unit 42. In S210, in such a case, the center of the extracted range (selected range) is gradually moved from the position of the black spot in the same figure in the direction of the black triangle by means of image movement processor 7122. Then, in the case that, even if it is moved a distance that is a specified fraction of the distance between the previous recognized position and the center of gravity, for example, 70%, the region shown in black in the extracted image remains narrow, as before, the output of the previous time will be re-outputted (S213). On the other hand, if as a result of shifting the extracted range (selected range), both the height and width of the region shown in black in the extracted image come to exceed their respective specified threshold values, as shown in Fig. 20, the head position for this iteration is determined from the extracted image of that time (S211). For example, a position in the center of the region shown in black in the selected image and a few pixels down from the top is selected as the head position for this iteration. Afterward, filter processing is performed on the head position of this iteration, which was selected (recognized) in this way, and the head position after filter processing is outputted (S212).

[0043] If the above approach is followed, as a general rule, a foundation position group is selected within the selected range corresponding to the recognized position of the previous time, and as an exception, the foundation position group is re-selected, changing the selection range. Even in the case that in the player image a moving object other than the player is image-captured, its influence can be rejected and even in the case that the head position has moved particularly quickly, appropriate position recognition can be done.

[0044] Next, in the above-described filter processing, as shown in Fig. 21A, a head position buffer is provided in main memory 26, and, by means of information updating part 7211, this buffer stores a maximum of 16 head positions (P_n through P_{n-15} ; where the appended characters correspond to the recognition time). This head position buffer is for storing the head positions of player P, recognized every specified time period, and in the buffer are stored in time sequence a maximum of 16 head positions, including the newest head position. Then, when the newest head position is recognized, that head position is additionally stored in the head position buffer and, at the same time, the oldest head position is discarded. For example, in the situation of Fig. 21A of the same figure, when head position P_{n+1} is recognized, that head position P_{n+1} is additionally stored in head position buffer and the oldest head position, P_n

15 is discarded from the head position buffer. In addition, with this head position buffer, the buffer size (in other words, the number of stored head position "units") is variable. In the present embodiment, for example, as shown in Fig. 21 B of the same figure, the states of 2 units, 4 units, and 8 units can be arranged, while as shown in Fig. 21 B of the same figure, the state of 16 units can be arranged, thus providing a total of four possible storage states.

[0045] As shown in Fig. 11, with the filter processing, first, n [head positions] are acquired, equal to the current buffer size of the head position buffer (S301). Then, if current buffer size n is equal to the maximum size N_{\max} (here, 16) (S302), by means of information updating part 7211, the oldest head position is discarded from the head position buffer, and the newest head position is additionally stored in the head position buffer (S305). On the other hand, if, as determined of buffer size determining part 7214, the current buffer size n is not equal to maximum size N_{\max} , the oldest head position is not discarded, but the newest head position is additionally stored in the head position buffer (S303), and 1 is added to the current buffer size of n (S304).

[0046] Next, the amount of movement of each head position stored in the head position buffer is calculated (S306). Specifically, by means of movement amount calculator 7212, the distance between each head position and the head position immediately preceding it is calculated. For example, in the example of Fig. 21, the distance between head position P_n and head position P_{n-1} , the distance between head position P_{n-1} and head position P_{n-2} , the distance between head position P_{n-2} and head position P_{n-3} , ..., and the distance between head position P_{n-14} and P_{n-15} are calculated. (In the case that 16 pieces of data are not all there (for example, if some are discarded), it is performed with the available data.) In addition, movement amount calculator 7212 calculates an average of the calculated movement amounts and next, by means of buffer size determining part 7213, buffer size N corresponding to that value is determined (S307). In the present embodiment, if the average value is 11 or more, the buffer size is set at $N=2$; if 9 or more, but under 11, buffer size is set at $N=4$; if 7 or more, but under 9, buffer size is set at $N=8$; and, if under 7, buffer size is set at $N=16$. Note that here it has been arranged such that buffer size N is determined based on the average of the movement amounts of the head positions stored in the head position buffer, but it would be acceptable to adopt another calculation method. For example, it would be acceptable if the movement amount of each head position were given weight, and the objects of movement amount calculations were limited to comparatively new ones from among the head positions stored in the head position buffer. In this way, it could be arranged that, in cases where it is determined that the newest head position moved suddenly, buffer size N would immediately decrease in size.

[0047] Next, buffer size determining part 7214 compares the current buffer size n and buffer size N (S308). If current buffer size n is larger than buffer size N , head positions stored in the head position buffer are discarded in order from the oldest ones, so that current buffer size n becomes buffer size N (S309). On the other hand, if current buffer size n is equal to or less than N , S309 is skipped. Afterward, the head positions stored in the head position buffer are averaged and those values are stored in main memory 26 as "previous output" (S311) and are outputted as filter processed head positions (S312). As explained above, the filter processed head positions are used in determining viewpoint position when a 3-dimensional space is plotted. In addition, they are used when determining the display position of present recognized position marker 54 when displaying player standing position guide image 50 in the title screen. Note that, here, the average value of head positions stored in the head position buffer is considered to be the filter processed head position. However, it would also be acceptable to attach weight to the head positions stored in the head position buffer, for example making it such that the influence of the newest head position in determining the filter processed head position would be greater.

[0048] Because, through the above-described filter processing, it was made such that an average value of head positions stored in the head position buffer is outputted, it is possible to suppress variation in the value of the filter processed head position. In addition, because it was made such that the size of the head position buffer changes according to the movement amounts of the head positions stored in that head position buffer, in the case that the head position of player P moves suddenly, the value of the filter processed head position can be made to change quickly in response to that. For that reason, it becomes possible to perform game processing advantageously using a filter processed head position.

[0049] Then, the position information obtained by viewpoint change processor 73 is sent to image processor 16. In this way, the viewpoint of a simulated camera in a simulated 3-dimensional space can be established in image processor 16, based on information inputted as explained above, and display processing of images viewed from that viewpoint is accomplished.

[0050] Note that the present invention is not limited to the above-described embodiments.

(1) For camera unit 42, two camera devices separated by a certain distance and placed so that their shooting directions cross each other (preferably crossing at a right angle) may be used. They should be arranged so that from their respective player images, the two-dimensional movement of the marked region is calculated, with one camera (pointed in the same direction as monitor 18) capturing up/down and transverse movement, while the other camera

(pointed to cross the screen of monitor 18) is pointed such that it acquires depthwise movement, relative to monitor 18. By doing this, 3-dimensional player movement can be detected and it is possible to move the simulated camera viewpoint inward and outward, in addition to up/down and right/left.

(2) In the present embodiment, for the game images, images in a 3-dimensional space were used, but the present invention can also be applied to games played in 2-dimensional space, and in that case images can be moved up/down or right/left in the screen.

(3) In the above description an example was presented in which the present invention was applied to a gun shooting game, but it could be applied to any kind of game as long as images are acquired by an image capturing means and the game proceeds based on those images

(4) Here player P's head was used as the object whose position was recognized, but another part may be used as the object of position recognition. Moreover, any object which player P holds in his hand, for example a toy golf club, a toy tennis racket, or a toy gun, etc. may be used as the object of position recognition

[0051] In summary, the present invention relates to a video game apparatus including a display for displaying images; a display control means for creating game images as seen from a simulated camera viewpoint and displaying said images on the screen of the display; and a game control part for conducting the game in response to reactions of a player responsive to the images displayed on the display. The video game apparatus of this invention comprises: an image capture means which can be arranged in such an orientation that its field of view is the play area in front of the display screen, and which periodically captures an image of the play area in the state thus arranged; a position detecting means for detecting from the captured images the position of a player's marked region; a movement detecting means for detecting two-dimensional movement of the position of the marked region thus detected; and a viewpoint changing means for moving the simulated camera viewpoint, in conjunction with the change direction and change amount of the position of the detected marked region.

[0052] The present invention takes another form. That is a method for controlling movement of a simulated camera viewpoint in a video game that is conducted by creating game images as seen from a simulated camera viewpoint, and displaying the images on the display while moving the simulated camera viewpoint in response to reactions of a player responsive to the images displayed on the display, the method comprising the steps of: while periodically capturing images of the play area by means of an image capturing means positioned in a desired position so that its orientation is such that

its field of view is the play area in front of the display screen, detecting a player's marked region from these captured images; further detecting two-dimensional movement of the position of the marked region; and moving the simulated camera viewpoint in conjunction with the direction of change and amount of change of the position of the detected marked region.

[0053] According to the aforementioned features, game images, for example 3-dimensional images, from the simulated camera viewpoint are created. These images are displayed on the screen of a display and the game proceeds while the simulated camera viewpoint moves due to player response, for example change in player stance, as player responds to the images displayed on above-mentioned display. In addition, images of the play area are periodically captured by means of an image capturing means positioned in a desired position so that its orientation is such that its field of view is the play area in front of the display screen. Then, from these captured images, the player's marked region for example his head, is detected and, additionally, two-dimensional movement of the position of the above-mentioned marked region is detected. The simulated camera viewpoint is moved so that above-mentioned simulated camera viewpoint points to the position of the detected marked region that is, it is linked to (made to follow) the direction of change and amount of change of the simulated camera. According to the invention described in the above, the image capture means can be readily mounted in a desired position relative to the display, and images can be constructively presented from the player's intended viewpoint, as though the simulated camera viewpoint is made to follow the player's free movement. In this way, the scope of game play can be broadened and games can be provided which are rich in interest and realism.

[0054] In the above described invention, the player's marked region can be the player's head. With this configuration, because the movement of the player's head, and thus his eyes, corresponds to the simulated camera viewpoint, movement of the viewpoint becomes realistic. As a result, because the viewpoint of the simulated camera and the movement of the player's head (that is, his eye position) can be matched, a more realistic viewpoint movement can be achieved.

[0055] Furthermore, in the above invention, the operational contents from a controller capable of external control can be to be reflected in the progress of the game. With this configuration, by conducting the game content through operation of a control part, such as a model gun, functioning as a game controller, the game becomes one richer in content variation. With the aforementioned feature, game content is carried out through operation of a control part, such as a model gun, etc., functioning as a game controller, and games can be provided which are richer in content variation.

[0056] In addition, in the above invention, it may be possible that the image capture means includes first and

second image capture means separated by a specified distance and arranged so that their directions intersect, and 3-dimensional movement of the player's marked region is detected from player images obtained by the first and second image capture means. With this configuration, because 3-dimensional movement of the player can be detected, it becomes possible to move the simulated camera viewpoint in the inward-outward direction in addition to the up/down and transverse directions, and the effect is a more realistic performance, especially in cases where the game images are 3-dimensional. With the aforementioned feature, because player's 3-dimensional movement can be detected, depthwise movement of the simulated camera viewpoint in addition to up/down and transverse movement (in other words, 3-dimensional movement) is possible.

[0057] The present invention can take another form which is a recording medium which stores a program for having a computer execute the method for controlling movement of a simulated camera viewpoint in a video game as recited in the above descriptions.

[0058] Although the present invention has been fully described by way of example with reference to the accompanying drawings, it is to be understood that various changes and modifications will be apparent to those skilled in the art. Therefore, unless otherwise such changes and modifications depart from the scope of the present invention hereinafter defined, they should be construed as being included therein.

Claims

1. In a video game apparatus including a display having a screen for displaying images, display control means for creating game images as seen from a simulated camera viewpoint and displaying said images on the screen of said display; and a game control part for conducting the game in response to reactions of a player responsive to the images displayed on said display; said video game apparatus comprising:

image capture means which can be arranged in such an orientation that its field of view is a play area in front of the display screen, and said image capture means periodically captures an image of the play area in the state arranged; position detecting means for detecting from the captured images a position of a player's marked region; movement detecting means for detecting two-dimensional movement of said position of the marked region detected by said position detecting means; and viewpoint changing means for moving the simulated camera viewpoint, in accordance with the change direction and change amount of the

position of the detected marked region.

2. A video game apparatus according to claim 1, further comprising initial play position setup means for performing initial calibration processing to normalize the player's standing position.
3. A video game apparatus according to claim 2, wherein said initial play position setup means displays player standing position guide image on the screen and reference position region at a predetermined position in said player standing position guide image, and present position mark corresponding to a player's marked region, obtained from said position detecting means is superimposed on the player standing position guide image.
4. A video game apparatus according to claim 3, wherein when said present position mark is within the reference position region, said reference position region is displayed in a color differently than the color thereof when the present position mark is outside of the reference position region.
5. The video game apparatus according to one of the preceding claims, wherein the player's marked region is the player's head.
6. The video game apparatus according to any one of claims 1 to 5, wherein operational contents given by a controller capable of external control are reflected in the progress of the game.
7. The video game apparatus according to any one of claims 1 to 6, wherein the image capture means comprises first and second image capture means separated by a specified distance and arranged so that their directions intersect so that 3-dimensional movement of the player's marked region is detected from player images obtained by the first and second image capture means.
8. The video game apparatus according to one of the preceding claims, wherein said image capture means is formed in such a manner that it can be mounted on a desired position with respect to the display.
9. A method for controlling movement of a simulated camera viewpoint in a video game that is conducted by creating game images as seen from a simulated camera viewpoint, and displaying the images on said display while moving the simulated camera viewpoint in response to reactions of a player responsive to the images displayed on the display, said method comprising the steps of:

while periodically capturing images of the play

area by means of an image capturing means positioned in a desired position so that its orientation is such that its field of view is a play area in front of the display screen, detecting a player's marked region from these captured images; 5
detecting two-dimensional movement of the position of the marked region; and
moving said simulated camera viewpoint in accordance with the direction of change and amount of change of the position of the detected marked region. 10

10. The method according to claim 9, wherein the player's marked region is the player's head. 15

11. The method according to claim 9 or 10, wherein operational contents given by a controller capable of external control are reflected in the progress of the game. 20


12. The method according to any of claims 9 through 11, wherein the image capture means comprises first and second image capture means separated by a specified distance and arranged so that their directions intersect so that 3-dimensional movement of the player's marked region is detected from player images obtained by the first and second image capture means. 25

13. A recording medium storing a program for controlling movement of a simulated camera viewpoint in a video game that is conducted by creating game images as seen from a simulated camera viewpoint, and displaying the images on said display while moving the simulated camera viewpoint in response to reactions of a player responsive to the images displayed on the display, said program comprising the steps of: 30

while periodically capturing images of the play area by means of an image capturing means positioned in a desired position so that its orientation is such that its field of view is a play area in front of the display screen, detecting a player's marked region from these captured images; 45
detecting two-dimensional movement of the position of the marked region; and
moving said simulated camera viewpoint in accordance with the direction of change and amount of change of the position of the detected marked region. 50

55

FIG.1






FIG.3




FIG.4A




FIG.4B




FIG.4C




FIG.4D




FIG.5A




FIG.5B




FIG.5C




FIG.5D




FIG.6




FIG.7




FIG.8




FIG.9




FIG.10




FIG.11




FIG.12A




FIG.12B




FIG.12C




FIG.12D




FIG.13




FIG.14




FIG.15




FIG.16




FIG.17




FIG.18




FIG.19




FIG.20




FIG.21A





FIG.21B



(19)



Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 279 425 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
26.03.2003 Bulletin 2003/13

(51) Int Cl.7: **A63F 13/10**

(43) Date of publication A2:
29.01.2003 Bulletin 2003/05

(21) Application number: 02016211.1

(22) Date of filing: 18.07.2002

(84) Designated Contracting States:
**AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
IE IT LI LU MC NL PT SE SK TR**
Designated Extension States:
AL LT LV MK RO SI

- Okubo, Toru
Minato-ku, Tokyo (JP)
- Domitsu, Hideyuki
Minato-ku, Tokyo (JP)
- Yamano, Tomoya
Minato-ku, Tokyo (JP)

(30) Priority: 19.07.2001 JP 2001220312

(71) Applicant: Konami Corporation
Minato-ku, Tokyo (JP)


(74) Representative: Müller-Boré & Partner
Patentanwälte
Grafinger Strasse 2
81671 München (DE)

(72) Inventors:
• Oishi, Toshimitsu
Minato-ku, Tokyo (JP)

(54) **Video game apparatus, method and recording medium storing program for controlling movement of simulated camera in video game**

(57) A 3-dimensional video game apparatus comprises display 40 for displaying an image; image-processing means 16 for creating a 3-dimensional image from the viewpoint of a simulated camera and displaying that image on a display screen; and game controller 14 which conducts the game in response to reactions of the player, responsive to images displayed on display 40. The game apparatus further comprises camera unit 42 which can be arranged in such an orientation that its field of view is the play area in front of the display screen, and which periodically captures images of the play area in the state thus arranged; a position recognizing part which detects the player's head from the captured image, and detects the two-dimensional movement of the detected head position; and viewpoint change processor which moves the viewpoint of said simulated camera in conjunction with the change direction and change amount of the position of the detected marked region.

FIG.1



EP 1 279 425 A3



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 01 6211

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X A	US 6 009 210 A (KANG SING BING) 28 December 1999 (1999-12-28) * column 3, line 20 - line 42 * * column 6, line 61 - line 67 * * column 8, line 32 - line 49 * ---	1,2,5, 8-10,13 3	A63F13/10
X	WO 99 35633 A (VIDEO MOUSE GROUP ;FREY ROBERT D (US); VOCK CURTIS A (US); GREALIS) 15 July 1999 (1999-07-15) * page 3, line 24 - line 31 * * page 19, line 30 - page 20, line 16 * * page 26, line 28 - page 27, line 24 * * page 38, line 21 - page 39, line 6 * * page 40, line 1 - line 19 * ---	1,5-13	
X	PATENT ABSTRACTS OF JAPAN vol. 1997, no. 09, 30 September 1997 (1997-09-30) -& JP 09 138637 A (MITSUBISHI HEAVY IND LTD), 27 May 1997 (1997-05-27) * abstract * * paragraph [0039] * ---	1,5,6, 8-11,13	TECHNICAL FIELDS SEARCHED (Int.Cl.7)
A	US 5 616 078 A (OH KETSU) 1 April 1997 (1997-04-01) * column 4, line 59 - column 5, line 3 * * column 5, line 25 - line 37 * ---	1,6-9, 11-13	A63F G06F
A	US 5 686 942 A (BALL JAMES V) 11 November 1997 (1997-11-11) * column 3, line 30 - line 34 * * column 5, line 32 - column 6, line 17 * --- -/--	1,9,13	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 30 January 2003	Examiner Sindic, G
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 02 01 6211

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
A	US 6 176 782 B1 (LYONS DAMIAN M ET AL) 23 January 2001 (2001-01-23) * column 4, line 50 - line 54 * * column 5, line 50 - line 53 * * column 7, line 14 - line 32 * ---	2	
A	US 4 836 670 A (HUTCHINSON THOMAS E) 6 June 1989 (1989-06-06) * column 17, line 37 - line 57 * -----	3	
The present search report has been drawn up for all claims			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
Place of search THE HAGUE		Date of completion of the search 30 January 2003	Examiner Sindic, G
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.82 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 02 01 6211

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

30-01-2003

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 6009210	A	28-12-1999	NONE	
WO 9935633	A	15-07-1999	AU 2211799 A WO 9935633 A2	26-07-1999 15-07-1999
JP 09138637	A	27-05-1997	NONE	
US 5616078	A	01-04-1997	JP 2552427 B2 JP 7185131 A	13-11-1996 25-07-1995
US 5686942	A	11-11-1997	NONE	
US 6176782	B1	23-01-2001	EP 0961965 A2 WO 9932959 A2 JP 2001513244 T US 6283860 B1	08-12-1999 01-07-1999 28-08-2001 04-09-2001
US 4836670	A	06-06-1989	US 4973149 A	27-11-1990

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82